

**TYPICAL FENCING NOTES:**

1. PROVIDE SHOP DRAWINGS FOR REVIEW AND APPROVAL PRIOR TO FABRICATION.
2. ALL FENCING FITTINGS SHALL BE INSTALLED IN ACCORDANCE WITH ASTM 626.
3. POSTS SHALL BE 3.0' (MIN.) EMBEDMENT SET IN 3,000-PSI (MIN.) CONCRETE FOOTERS.
4. ALL MEMBERS SHALL BE A.S.A. SCH. 40 GALVANIZED STEEL (VINYL COATING WHEN SPECIFIED ON PLANS).
5. ALL CHAIN LINE FENCE WALLS/MESH TO BE STRUNG THROUGH STRECHER BARS AND ATTACHED TO END POST WITH CLIPS AT 16" (MAX.) O.C.
6. CONTRACTOR SHALL INSTALL FENCE GROUNDING AND BONDING AS PER ARTICLE 250 OF THE NEC AND BUILDING DEPARTMENT REQUIREMENTS, LATEST EDITION.
7. MESH SHALL BE 9 GA. ALUMINIZED CHAIN LINK WIRE FABRIC 2" X 2" SQUARES ATTACHED TO POSTS AND TOP/BOTTOM RAILS (VINYL COATING WHEN SPECIFIED ON PLANS).
8. MESH SHALL BE WIRE TIED O.C. ALONG PIPE FRAME AT 24" (MAX.) ON TOP, 16" (MAX.) ON SIDES, 12" (MAX.) ALONG BOTTOM, AND AT EVERY POST TO PREVENT CURLING.
9. ALL CHAIN LINK MESH TERMINATION ENDS SHALL BE INSTALLED 1/4" (TYP.) FROM EDGE OF PERIMETER RAIL AND BE "KNUCKLED DOWN" TOP AND BOTTOM.
10. POST CAPS SHALL BE DRIVE-IN TYPE.
11. FRAMING FOR ALL ACCESS GATES SHALL BE WELDED AT ALL JOINTS AND HAVE HEAVY DUTY HINGES, LATCHES, AND LOCKING DEVICES.
12. ALL WELD POINTS SHALL BE CLEANED AND PAINTED WITH POWDERED ZINC PRIMER.
13. FENCE SHALL BE BONDED AND HAVE TWO WELL POINTS.

**GENERAL NOTES:**

1. TYPICAL FENCE POST SPACING IS 10'-0" O.C.
2. WHEN FENCE POSTS CANNOT BE SPACED 10'-0" O.C. OVER THE FULL LENGTH OF A SIDE THEN THE POSTS SHALL BE EVENLY SPACED O.C. WITH EACH POST LESS THAN 10'-0" APART.
3. ALL FABRIC TO BE GREEN POLYOLEFIN COATED #9 GAGE WIRE WOVEN IN A 2" MESH TOP AND BOTTOM EDGE TO BE TWISTED AND BARBED.
4. HEIGHT OF FABRIC TO BE FOR THE ENTIRE HEIGHT OF PROPOSED FENCE.
5. GREEN PVC OR METAL BOTTOM LOCKING PRIVACY SLAT SHALL BE INCLUDED WITH FENCE INSTALLATION.
6. CHAIN LINK FENCE SHALL HAVE GREEN COATED FINISH.

**TYPICAL WINDSCREEN NOTES:**

1. PROVIDE SHOP DRAWINGS FOR REVIEW AND APPROVAL PRIOR TO FABRICATION.
2. WIND SCREEN MATERIAL SHALL BE BLACK, COMMERCIAL GRADE UV-RESISTANT, HDPE OPEN MESH BLOCKING 80% VISIBILITY.
3. WIND SCREEN TO BE FOR THE ENTIRE HEIGHT OF PROPOSED FENCE INSTALLED CONTINUOUSLY AROUND COURTS ON THE PERIMETER FENCE AND ATTACHED TO FENCE 6" OFF THE BOTTOM OF THE FENCE.
4. ALL EDGES SHALL BE DOUBLE SOWN WITH 1.3" HEAVY TAPE REINFORCEMENT BINDING AND HAVE 1/2" I.D. BRASS GROMMETS THROUGH TAPE EVERY 16" HORIZONTALLY (TOP AND BOTTOM) AND EVERY 12" VERTICALLY (SIDES).
5. WHEN ATTACHING END PIECES TOGETHER, FULLY OVERLAP THE REINFORCING TAPE OF EACH END AND THEN THEY ARE TO BE ROLLED TOGETHER THREE TURNS (ROTATIONS) AND FASTENED WITH GROMMETS AT 12" O.C. BEFORE ATTACHING TO FENCE MESH.
6. HALF MOON AIR VENTS EVERY TEN FEET CENTERED ON SCREEN.
7. ZIP-TIE (HEAVY DUTY BLACK) GROMMETS AND REMOVE ZIP-TIE TRIMMINGS AND OLD ZIP-TIES.

CITY OF MARGATE, FLORIDA  
DEPARTMENT OF ENVIRONMENTAL  
AND ENGINEERING SERVICES

DATE: 08/24

DRAWN: KHA

**CHAIN-LINK FENCING AND MISC. NOTES**

U.O.N. = UNLESS OTHERWISE NOTED

