



NOTES:

1. ALL INTERLOCKING NINETY-DEGREE PARKING STALLS SHALL BE SEPARATED BY A CURBED LANDSCAPE MEDIAN NO LESS THAN SEVEN (7) FEET IN WIDTH. PARKING STALLS OF LESS THAN NINETY (90) DEGREES SHALL BE SEPARATED BY A CURBED MEDIAN WITH AN AVERAGE WIDTH OF SEVEN (7) FEET. THIS REQUIREMENT SHALL ONLY APPLY TO NEW DEVELOPMENTS AND REDEVELOPMENTS WITHIN THE CITY.

2. NO PARKING STALL SHALL BE LESS THAN NINE (9) FEET IN WIDTH AND EIGHTEEN (18) FEET IN LENGTH, EXCEPT THAT PARALLEL PARKING STALLS SHALL BE NO LESS THAN NINE (9) FEET IN WIDTH AND TWENTY-TWO (22) FEET IN LENGTH. ANY PARKING STALL ABUTTING A CURBED LANDSCAPE AREA NO LESS THAN SEVEN (7) FEET IN WIDTH MAY REDUCE STALL LENGTH BY TWO (2) FEET.

3. NO OFF-STREET PARKING AREA DRIVE-AISLE SHALL BE LESS THAN TWENTY-TWO (22) FEET IN WIDTH FOR TWO-WAY TRAFFIC. THE FOLLOWING STANDARDS SHALL APPLY TO ONE-WAY DRIVE AISLES IN PARKING AREAS:

- A. ONE-WAY DRIVE-AISLES FOR THIRTY-DEGREE ANGLED PARKING AND PARALLEL PARKING SHALL BE NO LESS THAN TWELVE (12) FEET IN WIDTH.
- B. ONE-WAY DRIVE AISLES FOR FORTY-FIVE-DEGREE ANGLED PARKING SHALL BE NO LESS THAN THIRTEEN (13) FEET IN WIDTH.
- C. ONE-WAY DRIVE AISLES FOR FIFTY-TWO AND ONE-HALF-DEGREE ANGLED PARKING SHALL BE NO LESS THAN 15 FEET IN WIDTH.
- D. ONE-WAY DRIVE AISLES FOR SIXTY-DEGREE PARKING SHALL BE NO LESS THAN SEVENTEEN (17) FEET IN WIDTH.
- E. ONE-WAY DRIVE AISLES FOR NINETY-DEGREE PARKING SHALL BE NO LESS THAN TWENTY-TWO (22) FEET IN WIDTH.

4. REFERENCE MARGATE CODE 40.705 OF MUNICODE FOR ALL OTHER PARKING REQUIREMENTS.

DATE: 12/24

DRAWN: KHA



CITY OF MARGATE, FLORIDA  
DEPARTMENT OF ENVIRONMENTAL  
AND ENGINEERING SERVICES

## PARKING SPACE AND DRIVE AISLES

G-33